

GX75 and GX95

Riding Mowers

(Serial No. 010001-)

John Deere Horicon Works
OMM117470 Issue H2

LITHO IN U.S.A.
ENGLISH

THANK YOU for purchasing a John Deere product.

READ THIS MANUAL carefully to learn how to operate and service your riding mower correctly. Failure to do so could result in personal injury or equipment damage.

THIS MANUAL SHOULD BE CONSIDERED a permanent part of your riding mower and should remain with the riding mower when you sell it.

MEASUREMENTS in this manual are U.S. customary units and their metric equivalents.

RIGHT-HAND AND LEFT-HAND sides are determined by facing in the direction the implement will travel when going forward.

WRITE IDENTIFICATION NUMBERS in the Specifications section. Accurately record all the numbers to help in tracing the riding mower should it be stolen. Your dealer also needs these numbers when you order parts. If this manual is kept on the riding mower, also file the identification numbers in a secure place off the riding mower.

WARRANTY is provided as part of John Deere's support program for customers who operate and maintain their equipment as described in this manual. The warranty is explained on the warranty certificate which you should have received from your dealer.

This warranty provides you the assurance that John Deere will back its products where defects appear within the warranty period. In some circumstances, John Deere also provides field improvements, often without charge to the customer, even if the product is out of warranty. Should the equipment be abused, or modified to change its performance beyond the original factory specifications, the warranty will become void and field improvements may be denied. Setting fuel delivery above specifications or otherwise overpowering machines will result in such action.

THE TIRE MANUFACTURER'S warranty supplied with your machine may not apply outside the U.S.



M47639
-UN-15JUN92

Contents

	Page		Page
Safety	1	MOWING, BAGGING, MULCHING	36
Controls	10	Service	
Operating Engine		John Deere Parts—Your Best Choice	44
Starting Engine	12	Service Intervals	45
Cold Weather Starting	14	Safety Tips—Servicing Mower and Riding Mower	45
Stopping Engine	15	Service—Miscellaneous	
Driving Riding Mower		Checking Tire Pressure	46
Avoid Damage to Painted Surfaces	16	Lubricate Front Axle Spindles	47
Locking and Unlocking Park Brake	16	Lubricate Rear Axles	47
Emergency Stopping	17	Adjusting Brake Pedal Linkage	47
Adjusting Seat	17	Service—Engine	
Traveling Forward or in Reverse	17	Checking Engine Oil Level	48
Shifting from Forward to Reverse	18	Changing Engine Oil	49
Using Clutch Pedal and Shift Lever	19	Adjusting Throttle Cable	50
Parking Riding Mower	19	Changing Fuel Filter	50
Operating Riding Mower		Cleaning Blower Screen	51
Raising and Lowering Mower	23	Checking and Cleaning Precleaner and air Cleaner Element	52
Setting Mower Height	24	Service—Electrical	
Adjusting Gauge Wheels(S)	24	Checking Spark Plug	54
Preparing Riding Mower for Leveling of Mower	25	Replacing Fuse	55
Adjusting Mower Level (Side-To-Side)	25	Checking Battery Electrolyte Level	56
Leveling Mower (Side-To-Side)	26	Cleaning Battery	57
Leveling Mower (Front-To-Rear)	26	Service—Mower and Blades	
Adjusting Mower Level (Front-To-Rear)	26	Check Adjustment of Mower Engagement Rod (PTO)	60
Engaging Mower	27	Adjusting Mower Engagement Rod—PTO	61
Disengaging Mower	27	Removing and Installing Mower Blades	62
Dismounting to Inspect or Unplug Mower	28	Sharpening Blades	63
Blade Recommendation	29	Balancing Blades	63
Mowing for a Better Lawn	29	Checking for Bent Blade	64
Mowing Tall Grass	30	Service—Mower Belts	
After Mowing	30	Checking Drive Belts	65
Transporting	31		
Fuel and Lubricants	32		

Continued on next page

All information, illustrations and specifications in this manual are based on the latest information available at the time of publication. The right is reserved to make changes at any time without notice.

OMM117470 H2-19-17JUL92

COPYRIGHT© 1992
DEERE & COMPANY
Moline, Illinois
All rights reserved
A John Deere ILLUSTRATION™ Manual

<https://www.ebooklibonline.com>

Hello dear friend!

Thank you very much for reading.

Enter the link into your browser.

The full manual is available for immediate download.

<https://www.ebooklibonline.com>

Contents

	Page
Removing Mower Belt	65
Installing Mower Belt	67
Preparing Riding Mower for Removal of Drive Belt	68
Removing Drive Belt	69
Installing Drive Belt	70
Removing Mower	72
Installing Mower	74
Troubleshooting	76
Storage	77
Crime Prevention	79
Assembly	81
Specifications	88
Index	

Safety

RECOGNIZE SAFETY INFORMATION

This is the safety-alert symbol. When you see this symbol on your machine or in this manual, be alert to the potential for personal injury.

Follow recommended precautions and safe operating practices.



DX,ALERT -19-04JUN90

T81389 -UN-07DEC88

UNDERSTAND SIGNAL WORDS

A signal word—DANGER, WARNING, or CAUTION—is used with the safety-alert symbol. DANGER identifies the most serious hazards.

DANGER or WARNING safety signs are located near specific hazards. General precautions are listed on CAUTION safety signs. CAUTION also calls attention to safety messages in this manual.



DX,SIGNAL -19-09JAN92

TS187 -19-30SEP88


FOLLOW SAFETY INSTRUCTIONS

Carefully read all safety messages in this manual and on your machine safety signs. Keep safety signs in good condition. Replace missing or damaged safety signs. Be sure new equipment components and repair parts include the current safety signs. Replacement safety signs are available from your John Deere dealer.

Learn how to operate the machine and how to use controls properly. Do not let anyone operate without instruction.

Keep your machine in proper working condition. Unauthorized modifications to the machine may impair the function and/or safety and affect machine life.

If you do not understand any part of this manual and need assistance, contact your John Deere dealer.



DX,READ -19-04JUN90

TS201 -UN-23AUG88



OPEI CERTIFICATION

This OPEI Label on your mower indicates that this model has been certified by an independent laboratory for compliance with American National Standard B-71.1-1990, "Safety Specifications" for Power Lawn Mowers, Lawn and Garden Tractors, and Lawn Tractors.



MX,CERT1 -19-02JUL92

M47634 -19-13MAY92

BACK UP SAFELY

ROTATING BLADES CAN CUT OFF ARMS OR LEGS

DO NOT MOW IN REVERSE UNLESS IT IS ABSOLUTELY NECESSARY.

BACK VERY CAREFULLY TO HELP PREVENT SERIOUS OR FATAL ACCIDENTS:

- FIRST: DISENGAGE the mower.
- THEN LOOK CAREFULLY over the entire area behind the tractor.
- LOOK DOWN AND BEHIND before and while backing.
- LOOK ESPECIALLY FOR CHILDREN.



MX,SAFU,A -19-21FEB92

M61420 -UN-01SEP88


DRIVE FORWARD SAFELY

ROTATING BLADES CAN CUT OFF ARMS OR LEGS

Keep CHILDREN and PETS out of mowing area.

Do not let CHILDREN ride on riding mower, or any attachment.

Do not let CHILDREN drive riding mower.



MX,SAFU,A1 -19-03APR92

M47291 -UN-10MAR92



CHECK GROUND CONDITIONS

Clear mowing area of objects that might be thrown. Keep people and pets out of mowing area.

Study mowing area. Set up safe mowing pattern. Do not mow under conditions where traction or stability is doubtful.

First, test drive area with PTO OFF and mower lowered. Slow down when you travel over rough ground.



MX,SAFU,E -19-12SEP90

M41423 -UN-30AUG88

AVOID TIPPING

Do not use mower near ditch or bank. Avoid holes, rocks, and roots.

Before you make sharp turns, slow down.

Install front weight before you use on slopes. Use up and down—not across slopes.

On slopes:

- Avoid sudden stops and starts.
- Be careful when you change directions.
- Avoid parking.



MX,SAJE,B -19-17JUL92

M41422 -UN-30AUG88

KEEP RIDERS OFF MACHINE

Only allow operator on machine. Keep riders off.

Riders on machine are subject to injury such as being struck by foreign objects and thrown off of machine.

Riders also obstruct operator's view resulting in machine being operated in an unsafe manner.



MX,SAJE,C -19-17JUL92

M61421 -UN-01SEP88



HANDLE FUEL SAFELY—AVOID FIRES

Handle fuel with care, it is highly flammable.

DO NOT refuel riding mower:


- While you smoke.
- When riding mower is near open flame or sparks.
- When engine is running. STOP engine.

Fill fuel tank outdoors.

Help prevent fires:

- Clean oil, grease and dirt from riding mower.
- Clean up spilled fuel immediately.

Do not store riding mower with fuel in tank in a building where fumes may reach an open flame or spark.



M73115 -UN-09MAR90


MX,SAJE,D -19-17JUL92

PREPARE FOR EMERGENCIES

Be prepared if a fire starts.

Keep a first aid kit and fire extinguisher handy.

Keep emergency numbers for doctors, ambulance service, hospital, and fire department near your telephone.



TS291 -UN-23AUG88

DX,FIRE2 -19-04JUN90




WEAR PROTECTIVE CLOTHING

Wear close fitting clothing and safety equipment appropriate to the job.

Prolonged exposure to loud noise can cause impairment or loss of hearing.

Wear a suitable hearing protective device such as earmuffs or earplugs to protect against objectionable or uncomfortable loud noises.

Operating equipment safely requires the full attention of the operator. Do not wear radio or music headphones while operating machine.



DX,WEAR -19-10SEP90

TS206 -UN-23AUG88


HANDLE CHEMICAL PRODUCTS SAFELY

Direct exposure to hazardous chemicals can cause serious injury. Potentially hazardous chemicals used with John Deere equipment include such items as lubricants, coolants, paints, and adhesives.

A Material Safety Data Sheet (MSDS) provides specific details on chemical products: physical and health hazards, safety procedures, and emergency response techniques.

Check the MSDS before you start any job using a hazardous chemical. That way you will know exactly what the risks are and how to do the job safely. Then follow procedures and recommended equipment.

(See your John Deere dealer for MSDS's on chemical products used with John Deere equipment.)



DX,MSDS,NA -19-15MAR91

TS1132 -UN-26NOV90




AVOID INJURY FROM CONTACTING BLADES

Before you dismount to unplug or adjust mower:

- Put shift lever at N (NEUTRAL) position.
- STOP engine.
- LOCK park brake.
- Pull PTO lever fully rearward.
- Remove key.
- Wait for mower blades to STOP.

Keep hands, feet and clothing away from mower deck when engine is running.

STOP mower blades when you are not using mower.



MX,SAJE,F -19-17JUL92

M41421 -UN-30AUG88

PRACTICE SAFE MAINTENANCE

Understand service procedure before doing work. Keep area clean and dry.

Never lubricate or service machine while it is moving. Keep hands, feet, and clothing from power-driven parts. Disengage all power and operate controls to relieve pressure. Lower equipment to the ground. Stop the engine. Remove the key. Allow machine to cool.

Securely support any machine elements that must be raised for service work.

Keep all parts in good condition and properly installed. Fix damage immediately. Replace worn or broken parts. Remove any buildup of grease, oil, or debris.

Disconnect battery ground cable (-) before making adjustments on electrical systems or welding on machine.



DX,SERV -19-04JUN90


TS218 -UN-23AUG88



WASTE PRODUCT SAFETY

Waste products, such as, used oil, fuel, coolant, brake fluid, and batteries, can harm the environment and people. See your local Recycling Center or John Deere dealer to learn how to recycle or get rid of waste products.

Don't use beverage containers for waste fluids—someone may drink from them.



MX,SAIR,I -19-17JUL92

M73469 -UN-24JAN91

READ SAFETY SIGNS



M38614 -19-18SEP90




GX95 Shown

M47640 -UN-15JUN92

MX,SAHR,A -19-17JUL92





! DANGER

ROTATING BLADE
DO NOT PUT HANDS OR FEET UNDER OR INTO MOWER WHEN ENGINE IS RUNNING

THROWN OBJECTS
BEFORE MOWING, CLEAR AREA OF OBJECTS THAT MAY BE THROWN BY BLADE

DO NOT OPERATE MOWER WITHOUT DISCHARGE CHUTE OR ENTIRE GRASS CATCHER IN PLACE



M47637 -19-09JUL92



M47641 -UN-15JUN92

GX95 Shown

MX,SAHR,B -19-17JUL92

! DANGER

EXPLOSIVE GASES Cigarettes, flames or sparks could cause battery to explode. Always shield eyes and face from battery. Do not charge or use booster cables or adjust post connections without proper instruction and training. Keep vent caps tight and level.

POISON

CAUSES SEVERE BURNS Contains sulfuric acid. Avoid contact with skin, eyes or clothing. In event of accident, flush with water and call a physician immediately. Keep out of reach of children.

M74408 -19-22APR92



M47694 -UN-15JUN92

GX95 Shown

MX,SAHR,C -19-17JUL92



⚠ DANGER

ROTATING BLADES CUT OFF ARMS AND LEGS

- Do not mow when children or others are around
- Do not mow at reverse
- Look down and behind before and while backing
- Never carry children

⚠ WARNING

AVOID SERIOUS INJURY OR DEATH

- Drive up and down slopes, not across
- Avoid sudden turns
- If machine stops going uphill, stop blade and back down slowly
- Keep safety devices (guards, shields, and switches) in place and working
- Read operator's manual
- When leaving machine:
 - Stop engine
 - Set park brake
 - Remove key

PARK

- Depress pedal
- Engage lever



GX95 Shown

M47642 -UN-15JUN92

M47703 -19-10JUN92

MX,SAHR,D -19-17JUL92

Controls

PEDALS

- A—Park Brake
- B—Brake Pedal
- C—Clutch



MX,CTJE,A -19-17JUL92

M74365 -UN-29JUN90

LEVERS AND SWITCH

- A—PTO Lever (Power Take Off—Mower engagement.)
- B—Shift Lever
- C—Ignition Key



MX,CTJE,B -19-17JUL92

M74366 -UN-29JUN90

- A—Throttle Lever
- B—Mower Lift Lever



MX,CTJE,C -19-17JUL92

M74367 -UN-29JUN90



Suggest:


If the above button click is invalid.

Please download this document first, and then click the above link to download the complete manual.

Thank you so much for reading

FUEL SHUT-OFF VALVE

A—Fuel Shut-Off Valve



GX75 Shown

M74387 -UN-02JUL90

MX,CTHR,A -19-17JUL92

<https://www.ebooklibonline.com>

Hello dear friend!

Thank you very much for reading.

Enter the link into your browser.

The full manual is available for immediate download.

<https://www.ebooklibonline.com>