

**2004 - 2006**



**SERVICE MANUAL**  
**SPORTSTER**  
**2004 - 2006**



**Suggest:**

**For more complete manuals. Please go to the home page.**

**<https://www.ebooklibonline.com>**

**If the above button click is invalid. Please download this document first, and then click the above link to download the complete manual.**

**Thank you so much for reading**

**1**

Chapter One  
General Information

**2**

Chapter Two  
Troubleshooting

**3**

Chapter Three  
Periodic Lubrication, Maintenance & Tune-up

**4**

Chapter Four  
Engine Top End

**5**

Chapter Five  
Engine Lower End

**6**

Chapter Six  
Primary Drive, Clutch & External Shift Mechanism

**7**

Chapter Seven  
Transmission & Internal Shift Mechanism

**8**

Chapter Eight  
Fuel, Emission Control & Exhaust Systems

**9**

Chapter Nine  
Electrical System

**10**

Chapter Ten  
Wheels, Tires & Drive Belt

**11**

Chapter Eleven  
Front Suspension & Steering

**12**

Chapter Twelve  
Rear Suspension

**13**

Chapter Thirteen  
Brakes

**14**

Chapter Fourteen  
Body

**15**

Chapter Fifteen  
Index

**16**

Chapter Sixteen  
Wiring Diagrams

**<https://www.ebooklibonline.com>**

Hello dear friend!

Thank you very much for reading.

Enter the link into your browser.

The full manual is available for immediate download.

**<https://www.ebooklibonline.com>**

**<https://www.ebooklibonline.com>**

Hello dear friend!

Thank you very much for reading.

Enter the link into your browser.

The full manual is available for immediate download.

**<https://www.ebooklibonline.com>**

# QUICK REFERENCE DATA

MODEL: \_\_\_\_\_ YEAR: \_\_\_\_\_

VIN NUMBER: \_\_\_\_\_

ENGINE SERIAL NUMBER: \_\_\_\_\_

CARBURETOR SERIAL NUMBER: \_\_\_\_\_

## TIRE INFLATION PRESSURE (COLD)\*

	PSI	kPa
Front wheel		
Rider only	30	207
Rider and passenger	30	207
Rear wheel		
Rider only	36	248
Rider and passenger	40	276

\*Tire pressure for original equipment tires. Aftermarket tires may require different inflation pressure.

## ENGINE OIL SPECIFICATIONS

Type	HD rating	Viscosity	Ambient operating temperature
HD Multi-grade	HD360	SAE 10W/40	Below 40° F
HD Multi-grade	HD360	SAE 20W/50	Above 40° F
HD Regular heavy	HD360	SAE 50	Above 60° F
HD Extra heavy	HD360	SAE 60	Above 80° F

## RECOMMENDED LUBRICANTS AND FLUIDS

Brake fluid	DOT 5
Front fork oil	HD Type E or equivalent
Fuel	
Type*	Unleaded
Octane	
XL883 models	Pump research octane of 87 or higher
XL1200 models	Pump research octane of 91 or higher
Transmission	
2004-2005	HD Sport Trans Fluid or equivalent
2006-on	HD Formulac Lubricant or equivalent

\*Refer to *Fuel Type* in Chapter Three.

### ENGINE AND PRIMARY DRIVE/TRANSMISSION OIL CAPACITIES

Engine oil with filter replacement	3.6 qt. (3.4 L)
Transmission oil (includes primary chaincase)	32 oz (946 ml)

### FRONT FORK OIL CAPACITY

Model	Capacity*
XL883L, XL1200L	12.3 oz. (364 ml)
All other models	11.6 oz. (342 ml)

\*Each fork leg.

### FUEL TANK CAPACITY

Model	Capacity*
XL883, XL883L, XL883R, XL1200R	3.3 gal. (12.5 L)
XL883C, XL1200C, XL1200L	4.5 gal. (17.0 L)

\*Including reserve.

### MAINTENANCE AND TUNE-UP SPECIFICATIONS

Item	Specification
Brake pad minimum thickness	0.04 in. (1.02 mm)
Clutch cable free play	1/16-1/8 in. (1.6-3.2 mm)
Drive belt deflection	
XL883, XL883R, XL1200R	3/8-7/16 in. (9.5-11.1 mm)
XL883C, XL883L, XL1200C, XL1200L	1/4-5/16 in. (6.4-7.9 mm)
Engine compression	
XL883 models	125-140 psi (862-966 kPa)
XL1200 models	200-225 psi (1380-1552 kPa)
Idle speed	950-1050 rpm
Ignition timing	Non-adjustable
Spark plug	HD-6R12*
Gap	0.038-0.043 in. (0.97-1.09 mm)

\*The manufacturer does not recommend another spark plug type.

### MAINTENANCE AND TUNE-UP TORQUE SPECIFICATIONS

Item	ft.-lb.	in.-lb.	N•m
Air filter cover screws	—	36-60	4.1-6.8
Air filter element retaining screws	—	40-60	4.5-6.8
Clutch inspection cover screws	—	84-108	9.5-12.0
Front fork cap	22-58	—	30-78
Front fork drain screw	—	13-17	1.5-2.0
Primary chain adjuster locknut	20-25	—	28-34
Primary chain inspection cover bolts	—	40-60	4.5-6.8
Rear axle nut*			
2004	60-65	—	81-88
2005-on	72-78	—	98-106
Spark plug	12-18	—	17-24
Transmission drain plug	14-30	—	19-40

\*Refer to procedure.

Thank you so much for reading.  
Please click the “Buy Now!”  
button below to download the  
complete manual.



After you pay.

You can download the most  
perfect and complete manual in  
the world immediately.

Our support email:

[ebooklibonline@outlook.com](mailto:ebooklibonline@outlook.com)