

NEW HOLLAND

MY16

MY17

MY19

**REPAIR
MANUAL**



MY16, MY17, MY19 REPAIR MANUAL CONTENTS

SECTION 1 - GENERAL INFORMATION

SECTION 2 - MODEL/SERIAL NUMBER LOCATION

SECTION 3 - GREASING AND LUBRICATION

SECTION 4 - TRANSAXLE

SECTION 5 - CHASSIS

SECTION 6 - MOWER DECKS

SECTION 7 - ELECTRICAL SYSTEM

The sections used through out all New Holland product Repair manuals may not be used for each product. Each Repair manual will be made up of one or several books. Each book will be labeled as to which sections are in the overall Repair manual and which sections are in the each book.

The sections listed above are the sections utilized for the MY16, MY17, and MY19 series tractors.

SECTION 1 - GENERAL INFORMATION

CONTENTS

Section	Description	Page
	General Information	1-2
	Think Safety First.....	1-2
	Garden Tractor Specifications	1-3
	Mower Specifications.....	1-7
	Hydrostatic Transaxle	1-9
	Torque Specifications	1-10
	Standard Torque For Dry, Zinc Plated, and Steel Fasteners (Inch Series).....	1-11
	Standard Torque For Dry, Zinc Plated, and Steel Fasteners (Metric Fasteners)	1-12
	Other Torque Specifications	1-13
	Equivalents and Conversions	1-14

<https://www.ebooklibonline.com>

Hello dear friend!

Thank you very much for reading.

Enter the link into your browser.

The full manual is available for immediate download.

<https://www.ebooklibonline.com>



This symbol means **WARNING** or **PERSONAL SAFETY INSTRUCTION** - read the instruction because it has to do with your safety. Failure to comply with the instruction may result in personal injury or even death.

This manual is intended as a service and repair manual only. The safety instructions provided herein are for troubleshooting, service, and repair of the MY16, MY17, MY19 tractors. The MY16, MY17, MY19 tractors and attachment operator's manuals contain safety information and operating tips for safe operating practices. Operator's manuals are available through your New Holland dealer.

THINK SAFETY FIRST

AVOID UNEXPECTED STARTING OF ENGINE...

Always turn off the engine and disconnect the spark plug wire(s) before cleaning, adjusting, or repair.

AVOID LACERATIONS AND AMPUTATIONS...

Stay clear of all moving parts whenever the engine is running. Treat all normally moving parts as if they were moving whenever the engine is running or has the potential to start.

AVOID BURNS...

Do not touch the engine, muffler, or other components which may increase in temperature during operation, while the unit is running or shortly after it has been running.

AVOID FIRES AND EXPLOSIONS...

Avoid spilling fuel and never smoke while working with any type of fuel or lubricant. Wipe up any spilled fuel or oil immediately. Never remove the fuel cap or add fuel when the engine is running. Always use approved, labeled containers for storing or transporting fuel and lubricants.

AVOID ASPHYXIATION...

Never operate an engine in a confined area without proper ventilation.

AVOID INJURY FROM BATTERIES...

Battery acid is poisonous and can cause burns. Avoid contact with skin, eyes, and clothing. Battery gases can explode. Keep cigarettes, sparks, and flames away from the battery.

AVOID INJURY DUE TO INFERIOR PARTS...

Use only original equipment parts to ensure that important safety criteria are met.

AVOID INJURY TO BYSTANDERS...

Always clear the area of bystanders before starting or testing powered equipment.

AVOID INJURY DUE TO PROJECTILES...

Always clear the area of sticks, rocks, or any other debris that could be picked up and thrown by the powered equipment.

AVOID MODIFICATIONS...

Never alter or modify any part unless it is a factory approved procedure.

AVOID UNSAFE OPERATION...

Always test the safety interlock system after making adjustments or repairs on the machine. Refer to the Electrical section in this manual for more information.

SECTION 1 - GENERAL INFORMATION

GARDEN TRACTOR SPECIFICATIONS

	MY16	MY17	MY19
ENGINE			
Type.....	Kohler	Kawasaki	Kawasaki
Model.....	CV460S	FH500V	FH5000
Horsepower.....	16.0 HP@3600 RPM	17.0 HP@3600 RPM	19.0 HP@3600 RPM
Cylinders.....	Single	Single	Double
Displacement.....	460CC	494CC	540CC
No Load Speed.....	3250 ±100 RPM	3250 ±100 RPM	3250 ±100 RPM
Electric Start.....	12V Bendix Drive	12V Bendix Drive	12V Bendix Drive
DC Alternator.....	15 amp regulated	13 amp regulated	13 amp regulated
Valve Rotators.....	Exhaust & Intake	Exhaust & Intake	Exhaust & Intake
Other.....	Cast iron sleeve, Smart choke, Dynamic balanced, Fuel pump, Solid mounted, Vertical shaft, Solid state ignition, Hydraulic lifters, Dry-type air cleaner w/ pre-cleander, Overhead valve, Separate choke and throttle, C.A.R.B. certified, Pressure lubricated with oil filter	Cast iron sleeve, Smart choke, Dynamic balanced, Fuel pump, Solid mounted, Vertical shaft, Electronic spark ignition, Hydraulic lifters, Dry-type air cleaner w/pre-cleander, Overhead valve, Separate choke and throttle, Solenoid fuel shut off, Dual element air cleaner, Fixed jet carburetor, C.A.R.B. certified, Pressure lubricated with oil filter	Cast iron sleeve, Smart choke, Dynamic balanced, Fuel pump, Solid mounted, Vertical shaft, Electronic spark ignition, Hydraulic lifters, Dry-type air cleaner w/ pre-cleander, Overhead valve, Temperature sensor, Separate choke and throttle, Solenoid fuel shut off, Dual element air cleaner, Fixed jet carburetor, C.A.R.B. certified, Pressure lubricated with oil filter
CONSTRUCTION			
Frame.....	Welded 2" x 2" x 1/4" angle frame	Welded 2" x 2" x 1/4" angle frame	Welded 2" x 2" x 1/4" angle frame
Other.....	Plastic console, Plastic hood and grille, Steel fender, Rubber footrest mats, V-511 Seat w/ springs, flip plate & no tool adjustment	Plastic console, Plastic hood and grille, Steel fender, Rubber footrest mats, V-511 Seat w/ springs, flip plate & no tool adjustment	Plastic console, Plastic hood and grille, Steel fender, Rubber footrest mats, V-511 Seat w/ springs, flip plate & no tool adjustment
FUEL SYSTEM			
Capacity.....	3.9 gals (14.7 l)	3.9 gals (14.7 l)	3.9 gals (14.7 l)
Type.....	Rear mounted tank	Rear mounted tank	Rear mounted tank
Other.....	Fuel shut-off valve, Fuel filter, Kelch cap w/top vent, 3" filler neck	Fuel shut-off valve, Fuel filter, Kelch cap w/ top vent, 3" filler neck	Fuel shut-off valve, Fuel filter, Kelch cap w/top vent, 3" filler neck, Electronic low fuel sensor

SECTION 1 - GENERAL INFORMATION

	MY16	MY17	MY19
TRACTION SYSTEM			
Transaxles	Hydro-Gear 330-3000 Hydrostatic	Hydro-Gear 330-3000 Hydrostatic	Hydro-Gear 330-3000 Hydrostatic
Ground Speed	@3250 RPM, 0-6.8- MPH (0-11.5 km/hr) for- ward, 0-3.2-MPH (0-5.1 km/hr) reverse	@3250 RPM, 0-6.8- MPH (0-11.5 km/hr) for- ward, 0-3.2-MPH (0-5.1 km/hr) reverse	@3250 RPM, 0-6.8- MPH (0-11.5 km/hr) for- ward, 0-3.2-MPH (0-5.1 km/hr) reverse
TIRES			
Rear Tires	23 x 10.50-12 Super turf tread	23 x 10.50-12 Super truf tread	23 x 10.50-12 Super truf tread
Front Tires	16 x 6.50-8 Super turf tread w/ball bearings	16 x 6.50-8 Super turf tread w/ball bearings	16 x 6.50-8 Super turf tread w/ball bearings
STEERING			
Steering Wheel	14" Comfort Grip	14" Deluxe Comfort Grip	14" Deluxe Comfort Grip
Front Wheel Spindle75" Dia.	.75" Dia.	.75" Dia.
Tilt Wheel	4 position	4 position	4 position
Turning Radius	16" (406.4 mm) RH & LH	16" (406.4 mm) RH & LH	16" (406.4 mm) RH & LH
Other	1.5 turns lock-to-lock	1.5 turns lock-to-lock	1.5 turns lock-to-lock
CONTROLS			
	Single lever attach- ment lift, All controls located for easy opera- tor access, Disk brake operated by neutral return/brake pedal, lever operated choke, Lever operated throttle, Single groove electric PTO clutch	Single lever attach- ment lift, All controls located for easy opera- tor access, Disk brake operated by neutral return/brake pedal, lever operated choke, Lever operated throt- tle, Single groove elec- tric PTO clutch, Cruise control	Single lever attachment lift, All controls located for easy operator access, Disk brake operated by neutral return/brake pedal, lever operated choke, Lever operated throttle, Single groove electric PTO clutch, Cruise con- trol
ELECTRICAL SYSTEM			
Battery Type	260CCA	340CCA	340CCA
Button Switch Inside Seat.	2 light warning system PTO and "KeyChoice"	4 light indicator system PTO and "KeyChoice", battery, cruise	6 light indicator system PTO and "KeyChoice", battery, cruise
Fuses	25 amp, Charge circuit 30 amp, Main circuit 10 amp, Light circuit 10 amp, Dash circuit	25 amp, Charge circuit 30 amp, Main circuit 10 amp, Light circuit 10 amp, Dash circuit	25 amp, Charge circuit 30 amp, Main circuit 10 amp, Light circuit 10 amp, Dash circuit

SECTION 1 - GENERAL INFORMATION

	MY16	MY17	MY19
Other.....	Bulb headlights, Rear reflectors, hourmeter	Bulb headlights, Rear reflectors, hourmeter	Bulb headlights, Rear reflectors, hourmeter
LUBRICATON FITTINGS			
Wheel Spindles.....	2 Fittings	2 Fittings	2 Fittings
Front Wheels	2 Fittings	2 Fittings	2 Fittings
Axle Pivot.....	1 Fittings	1 Fittings	1 Fittings
Hydro Pedal.....	N/A	1 Fitting	1 Fitting
DIMENSIONS			
Wheel Base	49.5" (1257.3 mm)	49.5" (1257.3 mm)	49.5" (1257.3 mm)
Tread Width	35.5" (901.7 mm) Front outside to outside 35.0" (889 mm) Rear outside to outside	35.5" (901.7 mm) Front outside to outside 35.5" (901.7 mm) Rear outside to outside	35.5" (901.7 mm) Front outside to outside 35.5" (901.7 mm) Rear outside to outside
Height	42.2" (1071.88 mm)	42.2" (1071.88 mm)	42.2" (1071.88 mm)
Width	35.5" (901.7 mm) (with- out mower)	35.5" (901.7 mm) (with- out mower)	35.5" (901.7 mm) (with- out mower)
Length.....	71.0" (1803.4 mm)	71.0" (1803.4 mm)	71.0" (1803.4 mm)
Ground Clearance	10.2" (259.08 mm) Front Axle 6.75" (171.45 mm) Rear Axle	10.2" (259.08 mm) Front Axle 6.75" (171.45 mm) Rear Axle	10.2" (259.08 mm) Front Axle 6.75" (171.45 mm) Rear Axle
WEIGHT			
Net Weight.....	530 lbs. (240.4 kg)	560 lbs. (254 kg)	580 lbs. (263 kg)
Shipping.....	614 lbs. (278.5 kg)	664 lbs. (301.2 kg)	664 lbs. (301.2 kg)
OPTIONAL EQUIPMENT			
Mowers			
Bagging Attachments			
Ground Tools			
Snow Attachments			
Kits			
Miscellaneous			
Accessories			
SAFETY			
Starter Interlocks	PTO Drive, Brake, Seat, Traction Drive	PTO Drive, Brake, Seat, Traction Drive	PTO Drive, Brake, Seat, Traction Drive
Operator Presence Interlock.....	PTO Drive, Traction Drive, NMIR, Meets ANSI B71.1-1998	PTO Drive, Traction Drive, NMIR, Meets ANSI B71.1-1998	PTO Drive, Traction Drive, NMIR, Meets ANSI B71.1-1998

SECTION 1 - GENERAL INFORMATION

MOWER SPECIFICATIONS


	42"	48"	52"
CONSTRUCTION			
Deck	12 gauge formed steel deck	12 gauge formed steel deck w/7 gauge reinforcement plate	12 gauge formed steel deck
Spindle Shafts	Three 17 mm diameter	Three 17 mm diameter	Three 25 mm diameter
Other	Relubable spindle bearings, Ground supported, Three front, Two rear anti-scalp rollers, Attaches to mid Attach-A-Matic hitch, Flip-up deflector	Relubable spindle bearings, Ground supported, Three front, Two rear anti-scalp rollers, Attaches to mid Attach-A-Matic hitch, Flip-up deflector	Relubable spindle bearings, Ground supported, Three front, Two rear anti-scalp rollers, Attaches to mid Attach-A-Matic hitch, Flip-up deflector
DIMENSIONS			
Cutting Width.....	41" (1041.4 mm)	47.1" (1196.34 mm)	52" (1320.8 mm)
Overall Width.....	54" (1371.6 mm) (deflector down) 49 inches (deflector up)	49" (1244.6 mm) (deflector down) 54 inches (deflector up)	65" (1651 mm) (deflector down) 58 inches (deflector up)
Cutting Height.....	1.0" to 4.0" (25.4 to 101.6 mm) (five positions)	1.0" to 4.0" (25.4 to 101.6 mm) (seven positions)	1.0" to 4.0" (25.4 to 101.6 mm) (seven positions)
Blade Tip Speed	15,772 fpm center blade @ 3250 RPM engine speed 16,730 fpm outside blades @3250 RPM engine speed	15,942 fpm center blade @ 3250 RPM engine speed 16,948 fpm outside blades @3250 RPM engine speed	16,647 fpm center blade @3250 RPM engine speed
Uncut Circle.....	53" (1346.2 mm) or less (LH) (16" tractor through radius)	44" (1117.6 mm) or less (LH) (16" tractor through radius)	29" (736.6 mm) or less (LH) (16" tractor through radius)
WEIGHT			
Unit.....	142 lbs. (64.4 kg)	165 lbs. (78.4 kg)	188 lbs. (85.3 kg)
Shipping	170 lbs. (77.1 kg)	195 lbs. (88.5 kg) (approx.)	216 lbs. (98 kg) (approx.)

SECTION 1 - GENERAL INFORMATION


	42"	48"	52"
SAFETY	Certified to ANSI B71.1-1996 standards	Certified to ANSI B71.1-1996 stan- dards	Certified to ANSI B71.1-1996 standards

SECTION 1 - GENERAL INFORMATION

HYDROSTATIC TRANSAXLES



GENERAL SPECIFICATIONS	
Lubrication	SAE 20W-50 API Classification SH/CD Oil
Oil Capacity	3.8 qts. (3.6 l)
Oil Level	The transaxle is a sealed system and does not require periodic checking. If the oil needs to be checked, IT CAN ONLY BE CHECKED COLD. There is a plug located on the right rear side of the transaxle. Using a 1/4 inch Allen wrench, slowly remove the plug. Oil level should be to the bottom of the port.





SECTION 1 - GENERAL INFORMATION

TORQUE SPECIFICATIONS

Recommended fastener torque values are listed in the following tables. For critical applications, as determined by New Holland, either the recommended torque or a torque that is unique to the application is clearly identified and specified in the service manual.

These torque specifications for the installation and tightening of fasteners shall apply to all fasteners which do not have a specific requirement identified in the service manual. The following factors shall be considered when applying torque: cleanliness of the fasteners, use of a thread sealant (Loctite), degree of lubrication on the fastener, presence of a prevailing torque feature, hardness of the surface underneath of the fastener's head, or similar condition which affects the installation.

As noted in the following tables, torque values should be reduced by 25% for lubricated fasteners to achieve the similar stress as a dry fasteners. Torque values may also have to be reduced when the fastener is threaded into aluminum or brass. The specific torque value should be determined based on the aluminum or brass material strength, fastener size, length of thread engagement, etc.



INCH SERIES BOLTS AND SCREWS	
(A) Grade 1	(C) Grade 8
(B) Grade 5	

METRIC BOLTS AND SCREWS	
(A) Class 8.8	(B) Class 10.9

The standard method of verifying torque shall be performed by marking a line on the fastener (head or nut) and mating part, then back off fastener 1/4 of a turn. Measure the torque required to tighten the fastener until the lines match up.

SECTION 1 - GENERAL INFORMATION

STANDARD TORQUE FOR DRY, ZINC PLATED, AND STEEL FASTENERS (INCH SERIES)

THREAD SIZE	GRADE 1, 5, & 8 WITH THIN HEIGHT NUTS	SAE GRADE 1 BOLTS, SCREWS, STUDS, & SEMS WITH REGULAR HEIGHT NUTS (SAE J995 GRADE 2 OR STRONGER NUTS)		SAE GRADE 5 BOLTS, SCREWS, STUDS, & SEMS WITH REGULAR HEIGHT NUTS (SAE J995 GRADE 2 OR STRONGER NUTS)		SAE GRADE 8 BOLTS, SCREWS, STUDS, & SEMS WITH REGULAR HEIGHT NUTS (SAE J995 GRADE 2 OR STRONGER NUTS)	
		In-lb	N-cm	In-lb	N-cm	In-lb	N-cm
# 6 - 32 UNC	10 ± 2	13 ± 2	147 ± 23	15 ± 2	170 ± 20	23 ± 2	260 ± 20
# 6 - 40 UNF				17 ± 2	190 ± 20	25 ± 2	280 ± 20
# 8 - 32 UNC	13 ± 2	25 ± 2	282 ± 30	29 ± 3	330 ± 30	41 ± 4	460 ± 45
# 8 - 36 UNF				31 ± 3	350 ± 30	43 ± 4	31 ± 3
# 10 - 24 UNC	18 ± 2	30 ± 5	339 ± 56	42 ± 4	475 ± 45	60 ± 6	674 ± 70
# 10 - 32 UNF				48 ± 4	540 ± 45	68 ± 6	765 ± 70
1/4 - 20 UNC	48 ± 7	53 ± 7	599 ± 79	100 ± 10	1125 ± 100	140 ± 15	1580 ± 170
1/4 - 28 UNF	53 ± 7	65 ± 10	734 ± 113	115 ± 10	1300 ± 100	160 ± 15	1800 ± 170
5/16 - 18 UNC	115 ± 15	105 ± 17	1186 ± 169	200 ± 25	2250 ± 280	300 ± 30	3390 ± 340
5/16 - 24 UNF	138 ± 17	128 ± 17	1446 ± 192	225 ± 25	2540 ± 280	325 ± 30	3670 ± 340
	ft-lb	ft-lb	N-m	ft-lb	N-m	ft-lb	N-m
3/8 - 16 UNC	16 ± 2	16 ± 2	22 ± 3	30 ± 3	41 ± 4	43 ± 4	58 ± 5
3/8 - 24 UNF	17 ± 2	18 ± 2	24 ± 3	35 ± 3	47 ± 4	50 ± 4	68 ± 5
7/16 - 14 UNC	27 ± 3	27 ± 3	37 ± 4	50 ± 5	68 ± 7	70 ± 7	68 ± 9
7/16 - 20 UNF	29 ± 3	29 ± 3	39 ± 4	55 ± 5	75 ± 7	77 ± 7	104 ± 9
1/2 - 13 UNC	30 ± 3	48 ± 7	65 ± 9	75 ± 8	102 ± 11	105 ± 10	142 ± 14
1/2 - 20 UNF	32 ± 3	53 ± 7	72 ± 9	85 ± 8	115 ± 11	120 ± 10	163 ± 14
5/8 - 11 UNC	65 ± 10	88 ± 12	119 ± 16	150 ± 15	203 ± 20	210 ± 20	285 ± 27
5/8 - 18 UNF	75 ± 10	95 ± 15	129 ± 20	170 ± 15	230 ± 20	240 ± 20	325 ± 27
3/4 - 10 UNC	93 ± 12	140 ± 20	190 ± 27	265 ± 25	359 ± 34	374 ± 35	508 ± 47
3/4 - 16 UNF	115 ± 15	165 ± 25	224 ± 34	300 ± 25	407 ± 34	420 ± 35	569 ± 47
7/8 - 9 UNC	140 ± 20	225 ± 25	305 ± 34	430 ± 45	583 ± 61	600 ± 60	813 ± 81
7/8 - 14 UNF	155 ± 25	260 ± 30	353 ± 41	475 ± 45	644 ± 61	660 ± 60	895 ± 81

NOTE: Reduce torque values listed in the table above by 25% for lubricated fasteners. Lubricated fasteners are defined as threads coated with a lubricant such as oil, graphite, or thread sealant such as Loctite.

NOTE: Torque values may have to be reduced when installing fasteners into threaded aluminum or brass. The specific torque value should be

determined based on the fastener size, the aluminum or base material strength, length of thread engagement, etc.

NOTE: The nominal torque values listed above for Grade 5 and 8 fasteners are based on 75% of the minimum proof load specified in SAE J429. The tolerance is approximately ± 10% of the nominal torque value. Thin height nuts include jam nuts.

SECTION 1 - GENERAL INFORMATION

STANDARD TORQUE FOR DRY, ZINC PLATED, AND STEEL FASTENERS (METRIC FASTENERS)

THREAD SIZE	CLASS 8.8 BOLTS, SCREWS, AND STUDS WITH REGULAR HEIGHT NUTS (CLASS 8 OR STRONG NUTS)		CLASS 10.9 BOLTS, SCREWS, AND STUDS WITH REGULAR HEIGHT NUTS (CLASS 10 OR STRONG NUTS)	
M5 x 0.8	57 ± 5 in-lb	640 ± 60 N-cm	78 ± 7 in-lb	885 ± 80 N-cm
M6 x 1.0	96 ± 9 in-lb	1018 ± 100 N-cm	133 ± 13 in-lb	1500 ± 150 N-cm
M8 x 1.25	19 ± 2 ft-lb	26 ± 3 N-m	27 ± 2 ft-lb	36 ± 3 N-m
M10 x 1.5	38 ± 4 ft-lb	52 ± 5 N-m	53 ± 5 ft-lb	72 ± 7 N-m
M12 x 1.75	66 ± 7 ft-lb	90 ± 10 N-m	92 ± 9 ft-lb	125 ± 12 N-m
M16 x 2.0	166 ± 15 ft-lb	225 ± 20 N-m	229 ± 22 ft-lb	310 ± 30 N-m
M20 x 2.5	325 ± 33 ft-lb	440 ± 45 N-m	450 ± 37 ft-lb	610 ± 50 N-m

NOTE: Reduce torque values listed in the table above by 25% for lubricated fasteners. Lubricated fasteners are defined as threads coated with a lubricant such as oil, graphite, or thread sealant such as Loctite.

NOTE: The nominal torque values listed above are based on 75% of the minimum proof load specified in SAE J1199. The tolerance is approximately ± 10% of the nominal torque value. Thin height nuts include jam nuts.

NOTE: Torque values may have to be reduced when installing fasteners into threaded aluminum or brass. The specific torque value should be determined based on the fastener size, the aluminum or base material strength, length of thread engagement, etc.

SECTION 1 - GENERAL INFORMATION

OTHER TORQUE SPECIFICATIONS

SAE GRADE 8 STEEL SET SCREWS

THREAD SIZE	RECOMMENDED TORQUE	
	SQUARE HEAD	HEX SOCKET
1/4 - 20 UNC	140 ± 20 in-lb	73 ± 12 in-lb
5/16 - 18 UNC	215 ± 35 in-lb	145 ± 20 in-lb
3/8 - 16 UNC	35 ± 10 ft-lb	18 ± 3 ft-lb
1/2 - 13 UNC	75 ± 15 ft-lb	50 ± 10 ft-lb

WHEEL BOLTS AND LUG NUTS

THREAD SIZE	RECOMMENDED TORQUE**	
7/16 - 20 UNF Grade 5	65 ± 10 ft-lb	88 ± 14 N-m
1/2 - 20 UNF Grade 5	80 ± 10 ft-lb	108 ± 14 N-m
M12 x 1.25 Class 8.8	80 ± 10 ft-lb	108 ± 14 N-m
M12 x 1.5 Class 8.8	80 ± 10 ft-lb	108 ± 14 N-m

** For steel wheels and non-lubricated fasteners.

**THREAD CUTTING SCREWS
(ZINC PLATED STEEL)**

TYPE 1, TYPE 23, OR TYPE F	
THREAD SIZE	BASELINE TORQUE*
No. 6 - 32 UNC	20 ± 5 in-lb
No. 8 - 32 UNC	30 ± 5 in-lb
No. 10 - 24 UNC	38 ± 7 in-lb
1/4 - 20 UNC	85 ± 15 in-lb
5/16 - 18 UNC	110 ± 20 in-lb
3/8 - 16 UNC	200 ± 100 in-lb

**THREAD CUTTING SCREWS
(ZINC PLATED STEEL)**

THREAD SIZE	THREADS PER INCH		BASELINE TORQUE*
	TYPE A	TYPE B	
No. 6	18	20	20 ± 5 in-lb
No. 8	15	18	30 ± 5 in-lb
No. 10	12	16	38 ± 7 in-lb
No.12	11	14	85 ± 15 in-lb

* Hole size, material strength, material thickness and finish must be considered when determining specific torque values. All torque values are based on non-lubricated fasteners.

Conversion Factors

in-lb x 11.2985 = N-cm

ft-lb x 1.3558 = N-m

N-cm x 0.08851 = in-lb

N-cm x 0.73776 = ft-lb

SECTION 1 - GENERAL INFORMATION

EQUIVALENTS AND CONVERSIONS

DECIMAL AND MILLIMETER EQUIVALENTS

FRACTIONS	DECIMALS	MM	FRACTIONS	DECIMALS	MM
1/64	0.015625	0.397	33/64	0.515625	13.097
1/32	0.03125	0.794	16/32	0.53125	13.484
3/64	0.046875	1.191	35/64	0.546875	13.891
1/16	0.0625	1.588	9/16	0.5625	14.288
5/64	0.078125	1.984	37/64	0.578125	14.684
3/32	0.9375	2.381	19/32	0.59375	15.081
1/8	0.1250	3.175	5/8	0.6250	15.875
9/64	0.140625	3.572	41/64	0.640625	16.272
5/32	0.15625	3.969	21/32	0.65625	16.669
11/64	0.171875	4.366	43/64	0.671875	17.066
3/16	0.1875	4.762	11/16	0.6875	17.462
13/64	0.203125	5.159	45/64	0.703125	17.859
7/32	0.21875	5.556	23/32	0.71875	18.256
15/64	0.234375	5.953	47/64	0.734375	18.653
1/4	0.2500	6.350	3/4	0.7500	19.050
17/64	0.265625	6.747	49/64	0.765625	19.447
9/32	0.28125	7.144	25/32	0.78125	19.844
19/64	0.296875	7.541	51/64	0.796875	20.241
5/16	0.3125	7.541	13/16	0.8125	20.638
21/64	0.328125	8.334	53/64	0.828125	21.034
11/32	0.34375	8.731	27/32	0.84375	21.431
23/64	0.359375	9.128	55/64	0.859375	21.828
3/8	0.3750	9.525	7/8	0.8750	22.225
25/64	0.390625	9.922	57/64	0.890625	22.622
13/32	0.40625	10.319	29/32	0.90625	23.019
27/64	0.421875	10.716	59/64	0.921875	23.416
7/16	0.4375	11.112	15/16	0.9375	23.812
29/64	0.453125	11.509	61/64	0.953125	24.209
15/32	0.46875	11.906	31/32	0.96875	24.606
31/64	0.484375	12.303	63/64	0.984375	25.003
1/2	0.5000	12.700	1	1.000	25.400
1 mm = 0.03937 in.			0.001 in. = 0.0254 mm		

SECTION 1 - GENERAL INFORMATION

U.S. METRIC CONVERSIONS

	TO CONVERT	INTO	MULTIPLY BY
Linear Measurement	Miles	Kilometers	1.609
	Yards	Meters	0.9144
	Feet	Meters	0.3048
	Feet	Centimeters	30.48
	Inches	Meters	0.0254
	Inches	Centimeters	2.54
	Inches	Millimeters	25.4
Area	Square Miles	Square Kilometers	2.59
	Square Feet	Square Meters	0.0929
	Square Inches	Square Centimeters	6.452
	Acre	Hectare	0.4047
Volume	Cubic Yards	Cubic Meters	0.7646
	Cubic Feet	Cubic Meters	0.02832
	Cubic Inches	Cubic Centimeters	28.3495
Weight	Tons (Short)	Metric Tons	0.9078
	Pounds	Kilograms	0.4536
	Ounces	Grams	28.3495
Pressure	Pounds/Sq.In.	Kilopascal	6.895
Work	Foot-pounds	Newton-Meters	1.356
	Foot-pounds	Kiogram-Meters	0.1383
	Inch-pounds	Kilogram-Centimeters	1.152144
Liquid Volume	Quarts	Liters	0.9463
	Gallons	Liters	3.785
Liquid Flows	Gallons/Minute	Liters/Minute	3.785
Temperature	Fahrenheit	Celsius	1. Subtract 32° 2. Multiply by 5/9



Suggest:

If the above button click is invalid.

Please download this document

first, and then click the above link

to download the complete manual.

Thank you so much for reading

SECTION 2 - MODEL/SERIAL NUMBER LOCATION

CONTENTS

Section	Description	Page
	Model/Serial Number Location	2-2

<https://www.ebooklibonline.com>

Hello dear friend!

Thank you very much for reading.

Enter the link into your browser.

The full manual is available for immediate download.

<https://www.ebooklibonline.com>